


Product number: 69080

NFC Sticker PET - On-Metal - 22 mm - NTAG215 - 540 Byte - white



Product information

The white PET On-Metal Sticker is the right choice for those who need a plain sticker for metallic surfaces. This sticker is particularly suitable for inventorying metallic objects due to its on-metal nature, as well as for use in marketing campaigns where the sticker needs to be applied to a metallic surface.

Short description

- PET material, flexible, 3M adhesive layer
- suitable for metallic/conductive surfaces
- 22 mm diameter
- Application indoor, conditionally also outdoor
- Ambient temperature from -25 to +70 degrees
- NXP NTAG215 (NTAG215) 540 Byte (NDEF: 480 Byte)

Product description

NFC product

The surface material of the white NFC sticker is made of PET. The material is therefore conditionally waterproof, so that the sticker can withstand moisture even in moderation. The sticker has a diameter of 22 mm and a material thickness of 0.41 mm. The antenna is easily visible from the outside, because the sticker is white. The chipset of the sticker is compatible with all current NFC-enabled smartphones.

NFC chip

The PET Sticker is equipped with the original NXP NTAG215, which occupies the midfield in the NTAG21x series and represents a good compromise between memory size and cost. The NXP NTAG21x series impresses with the greatest possible compatibility, good performance and intelligent additional functions. The NTAG215 has a total capacity of 540 bytes (free memory 504 bytes), of which usable memory in the NDEF is 480 bytes. Each individual chip has a unique serial number (UID) consisting of 7 bytes (alphanumeric, 14 characters). The NFC chip can be written up to 100,000 times and has a data retention of 10 years. The NTAG215 has the UID ASCII Mirror feature, which allows the tag's UID to be appended to the NDEF message, as well as an integrated NFC counter that automatically increments

Datasheet for NFC Sticker PET - On-Metal - 22 mm - NTAG215 - 540 Byte - white (69080)



during readout. Both features are not enabled by default. The NTAG215 is compatible with all NFC-enabled smartphones, the NFC21 tools and all ISO14443 terminals.

Total capacity: 540 byteFree memory: 504 byte

• Usable memory NDEF: 480 byte



Product properties

Product number	69080
Material thickness	0,40 mm (T)
Adhesive layer	Yes (3M)
Chip	NXP NTAG215
Functions	Write protection, UID ASCII Mirror, 32-bit Password, 24-bit Counter, ASCII Mirror, 7 Byte UID, ECC-based original signature, true anticollision, rewritable
Frequency	13.56 MHz
Memory	540 Byte (free: 504 Byte, NDEF: 480 Byte)
Weight	0,35 g
Data transfer rates	106 kbit/s
Storage temperature	Min -55°C - Max +125°C
Туре	Sticker
Chip standards / ISO Norm	ISO 14 443-3 A, ISO 14 443-2 A
On-metal	on metal
Operating temperature	Min -25°C - Max +70°C
Data retention	10 years
Number of write operations	100.000 times
Colour category	white
Detail colour	white glossy
Dimensions	22 mm Ø
Material	PET



Product form	round
Compatibility	to NFC-enabled smartphones: 100%
Further links	ntag
Antenna	Aluminium
NFC Forum Type	NFC Forum type 2
Delivery options	single



More images



