Product number: 68493

NFC Sticker PET - 22 mm - NTAG216 - 924 Byte - transparent



Product information

The transparent sticker made of PET can be easily applied to all smooth surfaces and is particularly suitable for marketing campaigns and identification due to its robustness.

Short description

- PET material, flexible, self-adhesive
- not suitable for metallic/conductive surfaces
- 22 mm diameter
- Indoor use, conditionally also outdoor use
- Ambient temperature from -25 to +70 degrees
- NXP NTAG216 (NTAG216) - 924 Byte (NDEF: 868 Byte)

Product description

NFC product

The surface material of the transparent NFC sticker is made of PET. The material is therefore conditionally waterproof, so that the sticker can withstand moisture even in moderation. The sticker has a diameter of 22 mm and a material thickness of 0.16 mm. The antenna is visible from the outside, because the sticker is transparent. The chipset of the sticker is compatible with all current NFC-enabled smartphones.

NFC chip

The PET sticker is equipped with the original NXP NTAG216, which offers the largest memory available in the NTAG21x series to date. The NXP NTAG21x series impresses with the greatest possible compatibility, good performance and intelligent additional functions. The NTAG216 has a total capacity of 924 bytes (free memory 888 bytes), of which usable memory in the NDEF is 868 bytes. Each individual chip has a unique serial number (UID) consisting of 7 bytes (alphanumeric, 14 characters). The NFC chip can be written up to 100,000 times and has a data retention of 10 years. The NTAG216 has the UID ASCII Mirror feature, which allows the tag's UID to be appended to the NDEF message, as well as an integrated NFC counter that automatically increments during readout. Both features are not enabled by default. The NTAG216 is compatible with all NFC-enabled smartphones, the NFC21 tools and all ISO14443 terminals.

- Total capacity: 924 bytes
- Free memory: 888 bytes
- Usable memory NDEF: 868 bytes

Product properties

Product number	68493
Chip	NXP NTAG216
Frequency	13.56 MHz
Detail colour	transparent
Colour category	transparent
Data transfer rates	106 kbit/s
Available colours	transparent
Storage temperature	Min -55°C - Max +125°C
Type	Sticker
Chip standards / ISO Norm	ISO 14 443-3 A , ISO 14 443-2 A
Operating temperature	Min -25°C - Max +70°C
Data retention	10 years
Material	PET
Product form	round
Compatibility	to NFC-enabled smartphones: 100%
Weight	1 g
Material thickness	0,16 mm (T)
Further links	ntag
Adhesive layer	Yes
Antenna	Aluminium
NFC Forum Type	NFC Forum type 2
Memory	924 Byte (free: 888 Byte, NDEF: 868 Byte)

More images



