

Product number: 68721

# NFC tag ABS - 40 x 32 mm - MIFARE DESFire EV1 4k - 4096 Byte - black | black



## Product information

Due to the integration of the MIFARE DESFire EV1 4k, the robust NFC tag ABS is often used in industry in areas with high security requirements, for example in access control or locking systems.

## Short description

- ABS material, rigid
- Format 40 x 32 mm, oval
- Indoor and outdoor use
- Ambient temperature from -25 to +70 degrees
- NXP MIFARE DESFire Chip EV1 4k

## Product description

### NFC product

The NFC tag is made of black ABS material and has a size of 40 x 32 mm with a material thickness of 4.3 mm. The NFC tag has a metal ring which makes it easy to attach. Due to the robust plastic material, the ABS tag is waterproof and is therefore ideal for both indoor and outdoor use.

### NFC chip

The ABS tag is equipped with the original MIFARE DESFire EV1 4k (MF3ICD41). The MIFARE DESFire series is intended for the realization of applications with high security requirements and offers corresponding security functions, which enable the protected storage of data on the chip. The MIFARE DESFire EV1 4k has a total capacity of 4096 bytes, which can be used by up to 28 applications. The DESFire EV1 4k chip has a 7-byte UID. The NFC chip can be written up to 500,000 times and has a data retention of 10 years. The chip is certified according to Common Criteria (EAL4+) and offers, among other things, 3-DES or AES128 compliant encryption. The MIFARE DESFire EV1 4k is compatible with all NFC-enabled terminals. Due to the special functions, special hardware (locking system) or software (app) is usually required for use. Please contact us to clarify the compatibility with your application.

- Total capacity: 4096 bytes
- Free memory: -

- Usable memory NDEF: -

## Product properties

<b>Product number</b>	68721
<b>Antenna format</b>	22 mm
<b>Dimensions</b>	40 x 32 mm (W x H)
<b>Frequency</b>	13.56 MHz
<b>Available colours</b>	black, blue
<b>Material thickness</b>	3,6 mm (T)
<b>Data transfer rates</b>	212 kbit/s, 106 kbit/s, 848 kbit/s, 424 kbit/s
<b>Storage temperature</b>	Min -55°C - Max +125°C
<b>Operating temperature</b>	Min -25°C - Max +70°C
<b>Data retention</b>	10 years
<b>Number of write operations</b>	100.000 times
<b>Detail colour</b>	black
<b>Weight</b>	4 g
<b>Colour category</b>	black
<b>Functions</b>	7 Byte UID
<b>Material</b>	ABS
<b>Compatibility</b>	to NFC-enabled smartphones: 100%
<b>Water resistance</b>	waterproof
<b>Product form</b>	oval
<b>Chip standards / ISO Norm</b>	ISO/IEC 7816
<b>Antenna</b>	Copper
<b>Type</b>	Keyfob

<b>Delivery options</b>	single
<b>Chip</b>	MIFARE DESFire EV1
<b>Memory</b>	4096 Byte

## More images